

Q20 SUPER MULTI-PURPOSE LUBRICANT



Q20

MOISTURE REPELLENT

Q20, the leading moisture repellent for protecting and removing moisture from wet ignition systems on cars, trucks, motorbikes, marine engines and electric motors. Q20 overcomes and prevents stubborn starting and stalling in damp climates and heavy downpours. Q20's unique penetrating power makes it ideal as a release agent and light duty lubricant for use in the home, garage and workshop, Q20 is silicone free.

Available in 150g and 300g aerosol. 5lt and 25lt drum.

Material Safety Data Sheet Q20 Aerosol

1 IDENTIFICATION

Manufacturer:	Triton-Leo Group (PTY)LTD, P.O. Box 459, Isando 1600 Tel: 011 452 7048 Fax: 011 452 8457
Chemical name:	Organic mixture
Trade name	Q20 Super Multi-Purpose Lubricant
1.1 Chemical characterisation	Organic mixture of highly refined mineral oil distillates of specific composition, which repels moisture, prevents corrosion, cleans and lubricates.
1.2 Colour:	Straw colour
1.3 Odour:	Mild oily solvent odour

2 COMPOSITION

The product contains the following materials apart from gases.			
	%Weight	Cas No	Chip (risk)
Chlorinated Hydrocarbons (WHITE SPIRIT)	54.72%	64742-82-1	R10
MINERAL OIL (REFINED)	18.20%	64742-65-0	N/A(for lubrication)
CARBON DIOXIDE AND R22(gases)	13 %	124-38-9	N/A
LUBRICANTS & JELLIES	2.08%	(RUST INHIBITORS)	
SOLVENTS	25%	(CLEANING PROPERTIES)	

3 HAZARDS IDENTIFICATION

3.1 Fire and Explosion	
Flash point:	Tag open cup 85°C (minimum)
Flammable limits:	(Lel)1.0% (Uel)6.0% (Solvent portion)
Extinguishing media:	CO ₂ , dry chemical, foam
Special fire fighting procedures:	See section 5 herein
Unusual fire and explosion	Flammable
3.2 Health/Routes of Entry	
Threshold limit value:	Hydrocarbon solvent lowest TLV(100ppm)
Carcinogenic:	The product has been assessed by independent laboratories as being human carcinogen category 3
3.3 Symptoms of Exposure	
Inhalation	May cause anaesthesia, headache, dizziness, nausea and upper Respiratory irritation
Skin contact:	May cause drying of skin and/or irritation
Eye contact:	May cause irritation, tears and redness
Ingestion:	May cause irritation, nausea, vomiting and diarrhoea
DANGER if swallowed can enter lungs and may cause chemical pneumonia. Do not induce vomiting. Obtain medical assistance.	

4 FIRST AID MEASURES

SKIN-	Wash copiously with soap and water – remove contaminated clothing, including Shoes and laundry before re-use. If skin irritation develops seek immediate
-------	--

EYES-	Medical attention. As soon as possible irrigate thoroughly with water for at least 15 minutes, holding the eyelid apart. If in any doubt, or the irritation persists, obtain medical attention
INHALATION-	Ensure that airways are clear and unobstructed. Keep warm and at rest. If there is any difficulty in breathing, or vomiting has occurred obtain medical attention urgently. If breathing stops or shows signs of failing, apply mouth to mouth ventilation.
INGESTION-	In the event of deliberate ingestion help must be obtained urgently.

Keep at rest. Do not induce vomiting but seek prompt medical attention. Observe patient in case abdominal pain develops, or patient starts to vomit. Try to keep patient conscious and try to make certain that patient does not aspirate vomit into lungs.

Material Safety Data Sheet Q20

5 FIRE-FIGHTING MEASURES

Keep product in storage (and in use) away from sources of ignition. In the event of fire, remove all unaffected product (if possible) away from the immediate vicinity. If necessary cool stocks with water mists. Extinguish burning material with foam, dry powder CO² or halons. **DO NOT USE WATER**
FIRST AID FACILITIES AND TREATMENT AS NORMAL FOR BURNS

6 ACCIDENTAL RELEASE MEASURES

- 6.1 Small Scale Spillages** In the unlikely event of spillages from aerosol cans, place cans in bags or open pail until pressure has dissipated. Aerosol cans must not be punctured or incinerated but disposed of in land fill or in accordance with local regulations. Do not wash Q20 contamination into drains and waterways. Instead wipe affected areas with white spirit or turpentine substitute and allow to dry. When dry wash affected areas with soapy water to remove any remnants of Q20. If white spirit cannot be applied, layer with sawdust or absorbent material. Allow to dry and then sweep/shovel into refuse bins and dispose of via public or private waste disposal.
- 6.2 Large Scale Spillages** In the event of large roadside transport spillages resulting from collision or overturned vehicles, vehicles must be kept away from contaminated roads or other surfaces. Affected areas should be covered in layers of sawdust or similarly absorbent material. Do not wash into drains, waterways or soil courses. Later remove absorbent material to waste disposal site. Marine spillages should be dealt with in accordance with pollutant procedures which are relevant to the product classification and IMDG codes.

7 HANDLING AND STORAGE

7.1 Special Handling Information

Ventilation: Must be sufficient to keep solvent vapour less than TLV
 Respiratory protection: Advised when concentration of solvent vapour exceeds TLV.
 Protective gloves: Advised when skin comes into contact with Q20 regularly or to prevent possible skin irritation.
 Eye protection: Factory or industrial users are advised to wear protection to guard Against potential eye contact i.e. goggles
 Other protection equipment: Overalls

7.2 Special storage information

There is no special storage information relevant to the keeping of Q20. It is obvious that aerosols should be kept away from sources of ignition or ambient temperatures above 50°celsius. Local laws and fire inspectorates may also influence storage policies of commercial organisations. Do not store large quantities of Q20 aerosol in unventilated bunkers or enclosures. Store in dry and cool areas. Keep out of reach of children. Do not spray on naked flame or any incandescent material. No smoking near expelled product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

See Section 7.1 above.

8.1 General

Keep product away from sources of ignition, avoid excessive inhalation of spray particles, do not puncture or store container above 50°celsius, keep away from children.
 Use only in accordance with the instructions printed on the container.
 Use only in a well ventilated area.
 Do not use near a naked flame or any incandescent material.
 Do not smoke whilst using.

8.2 Exposure Limits

Exposure Limit (EH40/97)

	8 hour TWA period		10 minute period	
	PPM	mgm-3	PPM	mgm-3
White spirit	100	575	125	720
Mineral oil	-	5	-	-

9 PHYSICAL AND CHEMICAL PROPERTIES Material Safety Data Sheet Q20 Aerosol

9 PHYSICAL AND CEMICAL PROPERTIES

Boiling point:	67°C
Vapour density (air=1):	Greater than 1
Solubility in water:	Insoluble
Specific gravity (H ₂ O=1)	1.126 @21°C
Volatile volume (by weight):	73.9%
Evaporation rate:	Not determined
Vapour pressure:	100 +/-5 psi celcius
Appearance:	Straw colour
Odour:	Mild oily solvent odour
Dielectric:	38 kva

10 STABILITY AND REACTIVITY

Stability:	Considered stable
Conditions to avoid:	N/A
Incompatibility:	Incompatible with strong oxidising agents
Hazardous decomposition:	Thermal decomposition may yield carbon monoxide and/or carbon Dioxide.
Hazardous polymerisation:	Will not occur

11 TOXICOLOGICAL INFORMATION

Oral toxicity (of liquid):	LD50>5.0g/kg bodyweight (rat)
Biodegradability (including solvent):	Ready biodegradable (84% after 28 days)

12 ECOLOGICAL INFORMATION

Volatile organic compounds (weight):	72.92 of product contains VOCs
CFCs:	CFC free since 1981
Tins:	Contains 7% recycled steel and in turn are recyclable
Caps:	High density polypropylene which is recyclable
Corrugated:	Recyclable

13 DISPOSAL CONSIDERATIONS

Empty aerosol cans should not be punctured or incinerated. Bury in landfill. Oil based products should be disposed of to a licensed waste contractor. Soak up with sawdust. Any disposal route should comply with local bylaws and the requirements of environmental protection legislation. Collect into drums and burn soaked sawdust. Authorities to be informed e.g. atomic energy board and fire department

14 TRANSPORT INFORMATION

By sea: "Aerosols" Class 2 UNI 1950, Marine Pollutant
 Tariff no 3403-19(5) packing code 111 class 2
 By road "Aerosols" UNI 1950 Class 2 item 5°F ADR

15 REGULATORY INFORMATION

Chemical (Hazard Information and Packaging Regulation) 1994 No3247 and amendment 1996 No1092 Council Directive 88/379/EEC of 7 June 1988 relating to the Classification of Packaging and Council Directive 75/324/EEC. Relating to Aerosol Dispensers and Amendment 94/1EC: Classified as FLAMMABLE. Keep out of reach of children. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C Do not pierce or burn containers after use. Do not spray on naked flame or any incandescent material. Keep away from sources of ignition. -No smoking near product.

16 OTHER INFORMATION

We believe the statements, technical information and recommendations contain herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss damage or expense, direct or consequential, arising from its use. Before using the product, read information printed on the label. This product is manufactured according to Amended Aerosol Directive(75/324/EEC and 94/1/ec).

Q20 is a Trademark. Review every 12 months Revision date: 1 May 2009

Irving Benson Wolozinsky

Title: Technical Adviser/Sales Director

Date 15/05/2009